

WR274三相陆用发电机（12线）

频率/转速	50Hz (1500rpm)									60Hz (1800rpm)								
	常用40℃			峰值40℃			峰值27℃			常用40℃			峰值40℃			峰值27℃		
	常用125℃			备用150℃			备用163℃			常用125℃			备用150℃			备用163℃		
环境温升																		
星形串联（电压V）	380	400	415	380	400	415	380	400	415	416	440	480	416	440	480	416	440	480
星形并联（电压V）	190	200	208	190	200	208	190	200	208	208	220	240	208	220	240	208	220	240
三角形串联（电压V）	220	230	240	220	230	240	220	230	240	240	254	277	240	254	277	240	254	277
WR274C额定容量 (KVA)	100.0	100.0	100.0	106.0	106.0	106.0	110.0	110.0	110.0	112.5	117.5	125.0	116.3	125.0	132.5	120.0	127.5	137.5
额定功率 (K W)	80.0	80.0	80.0	84.8	84.8	84.8	88.0	88.0	88.0	90.0	94.0	100.0	93.0	100.0	106.0	96.0	102.0	110.0
效率 (%)	89.8	90.3	90.6	89.5	90.0	90.4	89.2	89.8	90.2	90.2	90.6	91.1	90.0	90.2	90.8	89.8	90.1	90.6
WR274D额定容量 (KVA)	114.0	120.0	114.0	121.0	127.0	121.0	125.0	130.0	125.0	131.3	137.5	146.3	137.5	145.0	156.3	142.5	150.0	158.8
额定功率 (K W)	91.2	96.0	91.2	96.8	101.6	96.8	100.0	104.0	100.0	105.0	110.0	117.0	110.0	116.0	125.0	114.0	120.0	127.0
效率 (%)	90.3	90.6	91.1	91.1	91.6	91.8	91.0	91.4	91.7	90.5	90.8	91.3	91.2	91.5	92.0	91.0	91.4	91.9
WR274E额定容量 (KVA)	140.0	140.0	140.0	145.0	145.0	145.0	150.0	150.0	150.0	160.0	167.5	178.8	170.0	175.0	187.5	175.0	181.3	193.8
额定功率 (K W)	112.0	112.0	112.0	116.0	116.0	116.0	120.0	120.0	120.0	128.0	134.0	143.0	136.0	140.0	150.0	140.0	145.0	155.0
效率 (%)	91.3	91.7	92.0	91.1	91.6	91.8	91.0	91.4	91.7	91.4	91.7	92.1	91.2	91.5	92.0	91.0	91.4	91.9
WR274F额定容量 (KVA)	160.0	160.0	160.0	170.0	170.0	170.0	175.0	175.0	175.0	181.3	190.0	206.3	187.5	200.0	212.5	192.5	206.3	218.8
额定功率 (K W)	128.0	128.0	128.0	136.0	136.0	136.0	140.0	140.0	140.0	145.0	152.0	165.0	150.0	160.0	170.0	154.0	165.0	175.0
效率 (%)	92.0	92.3	92.5	91.7	92.1	92.3	91.6	92.0	92.2	92.1	92.4	92.7	92.0	92.2	92.6	91.9	92.1	92.5
WR274G额定容量 (KVA)	182.0	182.0	182.0	187.0	187.0	187.0	200.0	200.0	200.0	205.0	218.5	231.4	213.0	228.8	250.0	218.5	234.0	253.3
额定功率 (K W)	145.6	145.6	145.6	149.6	149.6	149.6	160.0	160.0	160.0	164.0	174.8	185.1	170.4	183.0	200.0	174.8	187.2	202.6
效率 (%)	92.0	92.4	92.6	91.9	92.2	92.5	91.7	92.1	92.3	92.2	92.4	92.7	92.0	92.2	92.5	91.9	92.1	92.5
WR274H额定容量 (KVA)	200.0	200.0	200.0	212.0	212.0	212.0	220.0	220.0	220.0	237.5	245.0	255.0	250.0	258.8	275.0	256.3	265.0	280.0
额定功率 (K W)	160.0	160.0	160.0	169.6	169.6	169.6	176.0	176.0	176.0	190.0	196.0	204.0	200.0	207.0	220.0	205.0	212.0	224.0
效率 (%)	93.0	93.3	93.4	92.8	93.1	93.3	92.7	93.0	93.2	93.0	93.2	93.6	92.8	93.1	93.4	92.7	93.0	93.3
WR274J额定容量 (KVA)	225.0	225.0	225.0	238.0	238.0	238.0	245.0	245.0	245.0	281.0	289.0	300.0	295.0	303.0	321.0	300.9	309.9	325.0
额定功率 (K W)	180.0	180.0	180.0	190.8	190.8	190.8	196.5	196.5	196.5	225.0	231.7	240.0	236.0	243.0	257.0	241.9	249.0	261.0
效率 (%)	92.4	92.6	92.6	92.6	92.4	92.6	92.7	92.4	92.4	92.8	92.8	92.8	92.6	92.6	92.6	92.4	92.4	92.4
WR274K额定容量 (KVA)	250.0	250.0	250.0	262.5	262.5	262.5	270.0	270.0	270.0	291.0	299.0	312.5	305.0	315.0	333.9	312.6	321.9	337.9
额定功率 (K W)	200.0	200.0	200.0	210.0	210.0	210.0	216.0	216.0	216.0	232.8	232.8	250.0	244.0	252.5	267.6	249.8	257.2	270.0
效率 (%)	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.8	92.6	92.9	92.8	92.8	92.8	92.8	92.8	92.8

所有图形和重量仅供参考
如有疑问请与工厂联系

WR274单相H级温升125℃ (4线)

转 速	50Hz1500rpm		50Hz1500rpm		60Hz1800rpm		60Hz1800rpm	
功率因素	0.8		1.0		0.8		1.0	
电 压	220V—240V		220V—240V		220V—240V		220V—240V	
绕 组	05	05	05	05	06	06	06	06
功率/容量	KW	KVA	KW	KVA	KW	KVA	KW	KVA
WR274C	52.8	66.0	66.0	66.0	67.0	84.0	90.0	90.0
WR274D	59.2	74.0	74.0	74.0	77.0	96.0	100.0	100.0
WR274E	75.2	94.0	94.0	94.0	90.0	112.0	115.0	115.0
WR274F	88.0	110.0	110.0	110.0	108.0	135.0	135.0	135.0
WR274G	96.0	120.0	120.0	120.0	120.0	150.0	150.0	150.0
WR274H	112.0	140.0	140.0	140.0	125.0	156.3	156.3	156.3

WR274单相H级温升125℃ (12根线)

频率/电压	50HZ 230V		60HZ 220V		60HZ 230V		60HZ 240V	
功率因素	0.8							
绕 组	311		312		312		312	
功率/容量	KW	KVA	KW	KVA	KW	KVA	KW	KVA
WR274C	48.0	60.0	49.0	61.3	51.5	64.4	54.0	67.5
WR274D	54.4	68.0	57.6	72.0	60.0	75.0	63.0	79.0
WR274E	68.0	85.0	67.2	84.0	72.0	90.0	77.0	96.0
WR274F	76.8	96.0	78.0	97.5	82.5	103.1	87.0	109.0
WR274G	84.0	105.0	86.0	107.5	90.0	112.5	96.0	120.0
WR274H	96.0	120.0	102.0	127.5	108.0	135.0	114.0	142.5

注:所有陆用额定值是40℃, 海拔1000米内。

船用额定值是基于环境温度45℃, 连续运行。所以发电机都为4级。

所列的所有电压从单个的宽范围绕组中可获得, 也即通过12个出线端重组可获得。

其他电压范围的发电机要根据用户需要制造。